



GRiDCASE 2510

Main Features

- 5.6" Touchscreen Display
- Intel® Elkhart Lake
- Up to 16GB RAM
- Up to 1TB SSD
- Up to 8 Hours Battery Life
- Military D38999 Connectors as Standard
- Environmental: DEF STAN 00-35 & MIL-STD-810
- EMC: DEF STAN 59-411 & MIL-STD-461

Technical Specification

GRiD

RUGGED, CONFIGURABLE COMPUTING



WWW.GRIDUK.COM



GRID-SALES@GRIDUK.COM



+44 (0) 1628 810 230

Internal Specification	
Processor	Intel® Atom x6211E, 2 x 1.3/3.0GHz (Turbo) Intel® Atom E3930, 2 x 1.3/1.8GHz (Turbo) Intel® Atom E3826, 2 x 1.46GHz
Graphics	11th & 9th Generation Intel® UHD Graphics
Memory	Up to 16GB RAM
BIOS	AMI EFI Optional Password Protection
Storage	Up to 256GB Solid State Drive Software Encryption Available
Operating System	Microsoft Windows Linux
Expansion	None
Display	5.6" Touchscreen Display 1280 x 800, WXGA 16:10 Aspect Ratio
Keyboard	Backlit Sealed Keypad Enter/Escape Buttons Display Brightness Controls
Mouse	Resistive Touchscreen Integrated Thumbstick 2-Button Mouse
Power	9-36VDC 25W Maximum Power Consumption AC Power Supply for Laboratory Use Rugged AC Power Supply Option Available
Battery	Up to 8 hours (Hot-swappable for continuous use)
Interfaces	User Defined (Interfaces are configurable to suit each application. Please speak to us about your requirements)

Environmental Specification	
EMC	DEF STAN 59-411* MIL-STD-461*
Environmental	DEF STAN 00-35* MIL-STD-810*
Operating Temperature	-30°C to +70°C
Storage Temperature	-40°C to +90°C
Ingress Protection	IP68
Dimensions (WxDxH)	155 x 117 x 37mm
Weight	With Battery 0.9kg Without Battery 0.66kg

*Please enquire for specific details and levels passed



GRID

RUGGED, CONFIGURABLE COMPUTING

