



GRIDCASE 2515

Main Features

- 15" LED Backlit Display
- Intel® Core i7 Processor
- Up to 64GB RAM
- PCI/PCI Express Expansion
- Resistive Touchscreen Technology
- Military D38999 Connectors as Standard
- Environmental: DEF STAN 00-35 & MIL-STD-810
- EMC Profile DEF STAN 59-411 & MIL STD 461

Technical Specification

GRID

RUGGED, CONFIGURABLE COMPUTING



WWW.GRIDUK.COM



GRID-SALES@GRIDUK.COM



+44 (0) 1628 810 230

Internal Specification	
Processor*	Intel® Core i7-1185G7E 2.8/4.4GHz Intel® Core i5-1145G7E 2.6/4.1GHz Intel® Core i3-1115G4E 3.0/3.9GHz Intel® Core i7-8665UE 1.7/4.4GHz Intel® Core i5-8365UE 1.6/4.1GHz Intel® Core i3-8145UE 2.2/3.9GHz
Graphics	Intel® Iris Xe and UHD 620 Graphics
Memory	Up to 64GB
BIOS	AMI EFI Optional password protection
Storage	Up to 3 x 2TB removable Solid State Drives Hardware and Software Encryption Available
ROM	Optional DVD +/- RW
Operating System	Microsoft Windows Linux
Expansion	Up to 3 x PCI slots Up to 4 x PC/104 Plus or PCI-104 slots Up to 3 x PCI Express slots Up to 5 x Mini PCIe slots
Display	15" LED Backlit Display 1024 x 768, XGA 4:3 Aspect Ratio High Bright Option Available
Keyboard	12 Configurable Function Keys (F1 - F12) Keys Can Be Designed To Suit User Requirements
Mouse	Resistive Touchscreen (optional)
Power	9-36V DC Adjustable Maximum Power Consumption AC Power Supply for Laboratory Use Rugged AC Power Supply Option Available
Battery	Up to 8 hours (With Dual Battery Option)
Interfaces	User Defined (Interfaces are configurable to suit each application. Please speak to us about your requirements)

*Other Processors available on request

Environmental Specification	
EMC	DEF STAN 59-411** MIL-STD-461**
Environmental	DEF STAN 00-35** MIL-STD-810**
Operating Temperature	-20°C to +55°C
Storage Temperature	-40°C to +70°C
Ingress Protection	IP67
Dimensions (WxDxH)	350 x 330 x 72.5mm
Weight	With Battery 6.5kg Without Battery 6.06kg

**Please enquire for specific details and levels passed
(These are not the products limits)



GRID

RUGGED, CONFIGURABLE COMPUTING

GRiDCASE 2515

Technical Specification



WWW.GRIDUK.COM



GRID-SALES@GRIDUK.COM



+44 (0)1628 810 230